ΙΝΔΒΔ DENKO

Premium Trunking System SLIMDUCT SD

Premium trunking system SLIMDUCT SD provides ideal





3 sizes






5 colours







Ivory Anthracite Gray
RAL7044 RAL7016



ay Brown RAL6014



Black RAL9011



Capacity Indication

Item	Insulation	Insulated Copper Tube Size												
	Thickness	1/4"x3/8"	1/4"x1/2"	1/4"x5/8"	3/8"x5/8"	3/8"x3/4"	3/8"x7/8"	1/2"x1-1/8"	5/8"x1-1/8"	5/8"x1-1/4"	3/4"x1-1/4"	3/4"x1-1/2"	7/8"x1-1/2"	7/8"x1-5/8"
SD-77	10 x 10	1	1	1	1	-	-	-	-	-	-	-	-	-
	20 x 20	_	-	-	_	-	_	-	-	-	-	-	-	-
SD-100	10 x 10	2	1	1	1	1	1	-	-	-	-	-	-	-
	20 x 20	-	-	_	-	-	_	-	-	-	_	-	_	-
SD-140	10 x 10	3	2	2	2	1	1	1	1	1	1	1	1	1
	20 x 20	1	1	1	1	1	1	1	1	-	-	_	-	-

^{*} Includes drain hose (OD16mm)



Temperature Range

finishing touch to your AC/heat pump installation.

SLIMDUCT SD is fully provided with corrosion proofed stainless screws.



Screws are essential to keep the trunking protected permanently in any exterior environment.



Without the screw, duct cover could fall off due to UV deterioration, storm, pest, or any damageable elements.

Specific Features



Optional coloured screws will blend the system into indoor applications.



Flexible joint SF has more flexibility and workability than any other brand.



Specially designed cutter VD-2100 cuts both the cover and the base at the same time cleanly and safely.



Comes with most wide variety of fittings in the HVAC industry. Enables to complete the job for any complicated pipework.



Fittings come with a hook pin to prevent the cover from sliding off.

Fittings









INABA DENKI SANGYO CO., LTD.

Overseas Sales Department INABA DENKO Div

10F, 4-11-14, Itachibori, Nishi-ku, Osaka, Japan, 550-0012
Tel: +81-(0)6-4391-1951 Fax: +81-(0)6-4391-1958
E-mail: sales-inabadenko@inaba.co.jp https://www.inaba-denko.com/en/









